



N.V. DOTHÉE S.A.

RD-UNIFIX

Waterborne transparent impregnation primer

DESCRIPTION OF THE PRODUCT

USE	Waterborne onecomponent transparent impregnation primer, for porous and powdering supports, indoor and outdoor. To apply before a waterborne system. Based on acrylic resin dispersed in water.
FEATURES	Good fixing capacity - The dispersed particles are very small, so it allows a better penetration of the substrate.
SUBSTRATES	Porous substrates such as bricks, concrete, plaster and derivatives.
SYSTEM:	Primer: 1 impregnation coat of RD-UNIFIX. Topcoat: 1 or 2 coats of a waterborne paint or a waterproofing product

APPLICATION INSTRUCTIONS

PREPARATION OF THE SUBSTRATE:	The substrate has to be clean, dry and free of dust.
APPLICATION CONDITIONS	Outdoor: never apply if raining Ambient temperature: > 5°C R.H.: max. 80%
APPLICATION MEANS	Brush, roller or airless (nozzle: 011-015)
DILUTION :	Don't dilute.
CLEANING OF TOOLS:	Water
CONSUMPTION :	Ca. 10 m ² /L in function of the porosity of the substrate.
PARTICULARITIES	Mix before use.



TECHNICAL DATA

FINISH: The primer penetrates in the substrate and gives a glossy aspect.

COLOURS : Colourless

SOLIDS CONTENT : In weight: ca. 15%
In volume: ca. 15%

VOC CONTENT : Max 0g/L

DENSITY: Ca. 1.0

FLASH POINT : Not flammable.

VISCOSITY: 15 – 20 sec. (Ford 4 – 23°C)

DRYING TIME: On touch: 1 hour
Recoatable: 4 hours.

PACKING: 1 L – 5 L – 20L

STORAGE
STABILITY: 12 months in a frostfree place.

SAFETY DATA

The safety data sheet is available on request.

These specifications are given for information. Since the manufacturer is not able to check the right application of the products, he cannot accept any responsibility for it. This technical data sheet replaces all previous editions.