



N.V. DOTHÉE S.A.

RD-TENNISCRYL

Acrylic paint for tennis fields

DESCRIPTION OF THE PRODUCT

USE	Waterborne onecomponent acrylic paint for sports grounds, especially tennis fields.
FEATURES	Excellent flexibility - High mechanical resistance - High resistance against humidity and moss.
SUBSTRATES	Concrete and bitumen.
SYSTEM:	<p>Slightly porous supports: Direct application of 2 coats on the substrate, without primer.</p> <p>Very porous supports:</p> <ul style="list-style-type: none"> • Primer: 1 coat of impregnation RD-UNIFIX. • Topcoat: 2 coats of RD-TENNISCRYL.

APPLICATION INSTRUCTIONS

PREPARATION OF THE SUBSTRATE:	The substrate has to be clean, dry and free of dust.
APPLICATION CONDITIONS	<p>Outdoor: never apply if raining</p> <p>Ambient temperature: minimum 5°C / R.H.: max. 80%</p>
APPLICATION MEANS	Brush, roller or airless (nozzle: 013–015)
DILUTION:	Water.
CLEANING OF TOOLS:	Water.
CONSUMPTION :	6 to 8 m ² /Kg per coat.
PARTICULARITIES	Mix before use.

TECHNICAL DATA

FINISH:	Mat.
COLOURS :	See colour chart.
SOLIDS CONTENT :	In weight: ca. 67% In volume: ca. 57%
VOC CONTENT :	Max 55g/L
DENSITY:	Ca. 1.4
FLASH POINT :	Not flammable.
VISCOSITY:	100 KU.
DRYING TIME:	On touch: 1 hour Recoatable: 16 hours.
PACKING:	5 Kg – 20 Kg
STORAGE STABILITY:	12 months: keep away from heat and frost.

SAFETY DATA

The safety data sheet is available on request.

These specifications are given for information. Since the manufacturer is not able to check the right application of the products, he cannot accept any responsibility for it. This technical data sheet replaces all previous editions.