



N.V. DOTHÉE S.A.

RD-ROOF ACRYL

Acrylic paint for roofs

DESCRIPTION OF THE PRODUCT

USE	Waterborne onecomponent acrylic paint for roofs. The final film is anti-moss.
FEATURES	Very good adhesion - Very good outdoor durability.
SUBSTRATES	Suits on asbestos-cement roofs, shingles...
SYSTEM:	<p>Slightly porous substrates: Direct application of 2 coats on the substrate, without primer: the first coat must be diluted with 10% of water.</p> <p>Very porous surfaces:</p> <ul style="list-style-type: none"> • Primer: 1 coat of impregnation RD-UNIFIX • Topcoat: 2 coats of RD-ROOF ACRYL.

APPLICATION INSTRUCTIONS

PREPARATION OF THE SUBSTRATE:	The substrate has to be degreased, dry, brushed and the moss must be removed.
APPLICATION CONDITIONS	<p>Never apply in heavy sun. Ambient temperature: > 5°C R.H.: max. 80%</p>
APPLICATION MEANS	Brush, roller or airless (nozzle: 013–015)
DILUTION :	Water
CLEANING OF TOOLS:	Water
CONSUMPTION :	Ca. 5 m ² /L per coat in function of the porosity of the support.
PARTICULARITIES :	Mix before use.



TECHNICAL DATA

FINISH:	Satin gloss
COLOURS :	See colour chart.
SOLIDS CONTENT :	Weight: ca. 51 % Volume: ca. 41 %
VOC CONTENT :	Max 45g/L
DENSITY:	Ca. 1.20
FLASH POINT :	Not flammable.
VISCOSITY:	80-100 P (Brookfield 20 Rpm)
DRYING TIME:	On touch: 1 hour Recoatible: 16 hours. By dry and mild conditions, it can be possible to apply 2 coats in one day.
PACKING:	1 L- 4L - 20L
STORAGE STABILITY:	12 months in a frostfree place.

SAFETY DATA

The safety data sheet is available on request.

These specifications are given for information. Since the manufacturer is not able to check the right application of the products, he cannot accept any responsibility for it. This technical data sheet replaces all previous editions.