



N.V. DOTHÉE S.A.

RD-DECO ACRYL SATIN

Satin acrylic paint for inner walls

DESCRIPTION OF THE PRODUCT

USE	Waterborne onecomponent satin acrylic paint, for inner walls. Very appropriate for inside decoration and for protection of different kinds of substrates.
FEATURES	High covering capacity - Easy to apply because of a high percentage of binder - Easy to clean – No yellowing.
SUBSTRATES	Plaster, gyproc, bricks, concrete, old paints, wallpaper.
SYSTEM:	<p>Slightly porous substrates: Direct application of 2 coats on the substrate, without primer.</p> <p>Very porous substrates:</p> <ul style="list-style-type: none"> • Primer: 1 coat of impregnation RD-UNIFIX. • Topcoat: 2 coats of RD-DECO ACRYL SATIN

APPLICATION INSTRUCTIONS

PREPARATION OF THE SUBSTRATE:	The substrates has to be clean, dry, free of dust.
APPLICATION CONDITIONS	Ambient temperature: > 5°C R.H.: max. 80%
APPLICATION MEANS	Brush, roller or airless (nozzle: 013–015)
DILUTION :	Water
CLEANING OF TOOLS:	Water
CONSUMPTION :	Ca. 10 m ² /L per coat.
PARTICULARITIES	Mix before use.



TECHNICAL DATA

FINISH:	Satin gloss
COLOURS :	White
SOLIDS CONTENT :	In weight: ca. 57% In volume: ca. 43%
VOC CONTENT :	Max 80g/L
DENSITY:	Ca. 1.3
FLASH POINT :	Not flammable.
VISCOSITY:	100 - 150 P (Brookfield 20 Rpm)
DRYING TIME:	On touch: 2 hours Recoatable: 4 hours.
PACKING:	1 L – 2.5 L – 4L – 10L – 20L
STORAGE STABILITY:	12 months, keep away from frost.

SAFETY DATA

The safety data sheet is available on request.

These specifications are given for information. Since the manufacturer is not able to check the right application of the products, he cannot accept any responsibility for it. This technical data sheet replaces all previous editions.