



N.V. DOTHÉE S.A.

RD-DECO TEX

Acrylic latex for inner walls

DESCRIPTION OF THE PRODUCT

USE	Waterborne onecomponent acrylic latex, for inner walls and ceilings.
FEATURES	Good covering capacity - Very good whiteness - Uniform flat aspect.
SUBSTRATES	Plaster, gyproc, bricks, concrete, old paints, wallpaper.
SYSTEM:	Slightly porous surfaces: Direct application of 2 coats on the substrates, without primer. Very porous surfaces: <ul style="list-style-type: none">• Primer: 1 coat of impregnation RD-UNIFIX.• Topcoat: 2 coats of RD-DECO TEX

APPLICATION INSTRUCTIONS

PREPARATION OF THE SUBSTRATE:	The substrate has to be clean, dry, and free of dust.
APPLICATION CONDITIONS	Ambient temperature: > 5°C R.H.: max. 80%
APPLICATION MEANS	Brush, roller or airless (nozzle: 013–015)
DILUTION :	Water
CLEANING OF TOOLS:	Water
CONSUMPTION :	Ca. 7 m ² /L per coat.
PARTICULARITIES	Mix before use.



TECHNICAL DATA

FINISH:	Flat
COLOURS :	White
SOLIDS CONTENT :	In weight: ca. 51% In volume: ca. 31%
VOC CONTENT:	Max 30g/L
DENSITY:	Ca. 1.4
FLASH POINT :	Not flammable.
VISCOSITY:	100 P (Brookfield 20 Rpm)
DRYING TIME:	On touch: 1 hour Recoatable: 4 hours.
PACKING:	1 L – 2.5 L – 4L – 10L – 20L
STORAGE STABILITY:	12 months, keep away from frost.

SAFETY DATA

The safety data sheet is available on request.

These specifications are given for information. Since the manufacturer is not able to check the right application of the products, he cannot accept any responsibility for it. This technical data sheet replaces all previous editions.